

Revision Number: 004.0 Issue date: 09/12/2014

# 1. PRODUCT AND COMPANY IDENTIFICATION

IDH number:

Product name: **LOCTITE C 400 SN63 2C 0.81MM S** 

known as 63/37 C400 2C 0.81MM

0.5KG AM

Product type: Solder Wire Item number: MM00986 Restriction of Use: None identified Region: **United States** 

Company address: Henkel Corporation

One Henkel Way

Rocky Hill, Connecticut 06067

Contact information:

Telephone: (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center

386825

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

## 2. HAZARDS IDENTIFICATION

**EMERGENCY OVERVIEW** 

DANGER: CAUSES SKIN AND EYE IRRITATION.

MAY CAUSE DROWSINESS OR DIZZINESS.

SUSPECTED OF CAUSING CANCER.

MAY DAMAGE FERTILITY OR THE UNBORN CHILD.

CAUSES DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED

EXPOSURE.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2B
CARCINOGENICITY	2
REPRODUCTIVE TOXICITY	1B
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE	1





#### **Precautionary Statements**

Obtain special instructions before use. Do not handle until all safety precautions have been Prevention:

read and understood. Do not breathe dust or fumes. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area.

Wear protective gloves. Use personal protective equipment as required.

IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove person to fresh air and Response:

keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing. IF exposed or concerned: Get medical attention. If skin irritation occurs: Get medical attention. If eye irritation persists: Get medical attention.

Take off contaminated clothing.

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Storage: Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local

IDH number: 386825 Product name: LOCTITE C 400 SN63 2C 0.81MM S known as 63/37 C400 2C 0.81MM 0.5KG AM

Page 1 of 6

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

#### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Tin	7440-31-5	60 - 100
Lead	7439-92-1	30 - 60

<sup>\*</sup> Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

## 4. FIRST AID MEASURES

Inhalation: Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give

artificial respiration. If symptoms develop and persist, get medical attention.

Skin contact: Remove contaminated clothing and footwear. Immediately flush skin with

plenty of water (using soap, if available). If symptoms develop and persist, get

medical attention. Wash clothing before reuse.

Eye contact: Flush eye(s) immediately with plenty of water. If eye irritation persists, consult

a specialist.

**Ingestion:** DO NOT induce vomiting unless directed to do so by medical personnel.

Never give anything by mouth to an unconscious person. If symptoms develop

and persist, get medical attention.

Symptoms: See Section 11.

# 5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus.

**Unusual fire or explosion hazards:** In case of fire, keep containers cool with water spray.

Hazardous combustion products: High temperatures may produce heavy metal dust, fumes or vapours. The flux

medium will give rise to irritating fumes. Oxides of Metals in Section 2. Oxides

of carbon. Formaldehyde.

## 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** Do not let product enter drains.

Clean-up methods: Ensure adequate ventilation. Wear suitable protective clothing, gloves and

eye/face protection. Scrape up spilled material and place in a closed container

for disposal.

## 7. HANDLING AND STORAGE

**Handling:** Use only in well-ventilated areas. Wear suitable protective clothing, gloves and

eye/face protection. Avoid contact with eyes, skin and clothing. When using do not eat, drink or smoke. Wash hands before breaks and immediately after

handling the product.

Storage: Store in original container until ready to use.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Tin	2 mg/m3 TWA	2 mg/m3 PEL (as Sn)	None	None
Lead	0.05 mg/m3 TWA (as Pb)	0.05 mg/m3 TWA 0.03 mg/m3 OSHA_ACT	None	None

Engineering controls:

Use adequate ventilation to remove molten vapors or fumes.

**Respiratory protection:**Use an organic vapor respirator for concentrations exceeding the

Occupational Exposure Limit.

**Eye/face protection:** Safety goggles or safety glasses with side shields.

**Skin protection:** Disposable rubber or plastic gloves.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

 Physical state:
 Solid

 Color:
 Gray

 Odor:
 Metallic

 Odor threshold:
 Not available.

 pH:
 Not available.

 Vapor pressure:
 Not available.

 Boiling point/range:
 Not available.

 Melting point/ range:
 Not available.

Specific gravity: Vapor density: Not available. Flash point: Does not flash. Flammable/Explosive limits - lower: Not available. Flammable/Explosive limits - upper: Not available. Autoignition temperature: Not available. **Evaporation rate:** Not available. Solubility in water: Insoluble Partition coefficient (n-octanol/water): Not available. **VOC** content: 0 %; 0 g/l Viscosity: Not available. **Decomposition temperature:** Not available.

IDH number: 386825

## 10. STABILITY AND REACTIVITY

**Stability**: Stable under normal conditions of storage and use.

Hazardous reactions: Will not occur.

**Hazardous decomposition** 

products:

IDH number: 386825

Oxides of carbon. Oxides of Metals in Section 2. Formaldehyde.

**Incompatible materials:**Solder alloy will react with concentrated nitric acid to produce toxic fumes of nitrogen oxides.

Acids and bases. Oxidizing agents.

Reactivity: Not available.

Conditions to avoid: Avoid contact with acids and oxidizing agents. Solder alloy will react with concentrated nitric

acid to produce toxic fumes of nitrogen oxides.

#### 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes

#### Potential Health Effects/Symptoms

Inhalation: Fumes and/or dust produced by this product may be hazardous in case of ingestion or

inhalation. Rosin thermal decomposition product (as formaldehyde) is classified by NIOSH as a potential occupational carcinogen. Vapor overexposure may cause drowsiness. Dizziness. Lead is a cumulative poison and continuous exposure to small amounts over time can raise the body's content to toxic levels. Excessive exposure to tin fumes or dust may cause Stannosis, a chronic respiratory disease resulting in reduced lung capacity and benign tumors. Excessive inhalation of fumes from many metals can produce an acute reaction known as "metal fume fever". Symptoms consist of chills and fever (very similar to and easily confused with flu

symptoms) which come on a few hours after large exposures.

Skin contact: Causes skin irritation. Eye contact: Causes eye irritation.

**Ingestion:** Lead is a cumulative poison and continuous exposure to small amounts over time can raise the

body's content to toxic levels.

Hazardous Component(s) LD50s and LC50s		Immediate and Delayed Health Effects	
Tin	None	Gastrointestinal, Irritant, Kidney, Liver, Lung, Nervous System	
Lead	None	Behavioral, Blood, Developmental, Eyes, Gastrointestinal, Kidney, Liver, Muscle, Nervous System, Reproductive, Skin, Some evidence of carcinogenicity. Thyroid	

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Tin	No	No	No
Lead	Reasonably Anticipated to be a Human Carcinogen.	Group 2B	No

## 12. ECOLOGICAL INFORMATION

**Ecological information:**No specific studies have been conducted by Henkel on the ecotoxicity or

environmental fate of this material; however, commonly available data on the material indicate that uncontrolled releases to soil, ground water, or surface waters could entail acute and/or chronic ecological effects, depending on the quantity and concentration of such releases. Releases of volatile components

to the atmosphere are not believed to entail significant ecological

consequences provided such releases are within the exposure levels set forth in this document. Accordingly, all appropriate measures should be taken to avoid uncontrolled releases to the environment, and any spills or other uncontrolled releases which may occur should be contained and cleaned up

immediately in accordance with Section 6.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: D008: Lead

#### 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:
Hazard class or division:
Identification number:
Packing group:
Not regulated
None
None

International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated

Hazard class or division: None Identification number: None Packing group: None

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

## 5. REGULATORY INFORMATION

**United States Regulatory Information** 

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis CERCLA/SARA Section 311/312: Immediate Health, Delayed Health

CERCLA/SARA Section 313: This product contains the following toxic chemicals subject to the reporting requirements of

section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40

CFR 372). Lead (CAS# 7439-92-1).

CERCLA Reportable quantity: Lead (CAS# 7439-92-1) 10 lbs. (4.54 kg)

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This

product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

IDH number: 386825 Product name: LOCTITE C 400 SN63 2C 0.81MM S known as 63/37 C400 2C 0.81MM 0.5KG AM

Page 5 of 6

#### **Canada Regulatory Information**

IDH number: 386825

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

## 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Michele Oltra, Regulatory Affairs Specialist

**Issue date:** 09/12/2014

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.