TECH SHEET Page 1 of 1

Mold-Pac™

Description: DEACON Mold-Pac™ is a Damming, Molding, and

Positioning Putty. (BABBITRITE REPLACEMENT)

Features: Resistant to extreme temperatures, Can be easily and

quickly removed, Remains flexible and retains molten Babbitt and low melting point materials, Easily packed

in place, Holds tight, Asbestos-free.

Applications: Damming compound (for pouring Babbitt bearings,

epoxies, dielectric fluids, various molten alloys, etc.), Vibration suppression, Positioning delicate parts,

Holding solder while soldering wires on generators, Aids

in positioning during welding/brazing.

Packaging: 10 lb. container, 50 lb. pail.



FOR INDUSTRIAL USE BY PROFESSIONALLY TRAINED PERSONNEL ONLY. CONSULT MSDS & TECH SHEET FOR ALL SAFETY, TECHNICAL, & WARRANTY INFORMATION BEFORE USE. NOT RECOMMENDED FOR USE ON NUCLEAR APPLICATIONS

Disclaimer: The information & recommendations of Deacon concerning these products is based upon laboratory tests, customer feedback, and experience and to the best of our knowledge and belief are true and accurate. As the conditions of use are beyond the control of Deacon Industries, Inc. the company assumes no liability for damage caused by this product other than the replacement of the product or refund of the purchase price. The responsibility for determining whether or not the product is suitable for use rest solely with the purchaser. Deacon Industries, Inc., recommends that the product be tested prior to use. This product is intended for a temporary repair and no agent, representative or employee of the company is authorized to alter this provision which relates to goods delivered, whether sold, delivered as samples or otherwise.

sales@acrosales.com (877)-SOLDERS or (877) 765-3377